

### Features

- Planar photodiode
- Low capacitance
- Fast switching time
- Low leakage current
- Linear response vs irradiance
- TO-46 base with epoxy dome lens
- Multiple dark current ranges available



### Description

This planar, passivated silicon photodetector is designed to operate in either photovoltaic or reverse bias mode to provide low capacitance with fast switching speed. It provides excellent linearity in output signal versus light intensity. Low dark current and low capacitance make it the ideal detector for fast rise time applications.

### Absolute Maximum Ratings

Storage Temperature	-20°C to +75°C
Operating Temperature	-20°C to +75°C
Soldering Temperature (3)	260°C

- Notes: (1) Ee = light source @ 2854 °K  
 (2) Ee = light source @  $\lambda = 880 \text{ nm}$   
 (3) >2 mm from case for <5 sec.



### Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise noted)

Symbol	Parameter	MIN	TYP	MAX	UNITS	TEST CONDITIONS
I <sub>SC</sub>	Short Circuit Current	150	225		μA	V <sub>R</sub> =0V, Ee=25mW/cm <sup>2</sup> (1)
V <sub>OC</sub>	Open Circuit Voltage		0.40		V	Ee=25mw/cm <sup>2</sup> (1)
I <sub>D</sub>	Reverse Dark Current:					
	SLD-68E1A			100	nA	V <sub>R</sub> =100mV, Ee=0
	SLD-68E1B			100	nA	V <sub>R</sub> =5V, Ee=0
	SLD-68E1C			10	nA	V <sub>R</sub> =5V, Ee=0
	SLD-68E1D			1	nA	V <sub>R</sub> =5V, Ee=0
	SLD-68E1E			250	pA	V <sub>R</sub> =5V, Ee=0
C <sub>J</sub>	Junction Capacitance		40		pF	V <sub>R</sub> =0, Ee=0, f=1MHz
t <sub>R</sub>	Rise Time		1.0		μs	V <sub>R</sub> =10V, R <sub>L</sub> =1kΩ (2)
t <sub>F</sub>	Fall Time		1.5		μs	V <sub>R</sub> =10V, R <sub>L</sub> =1kΩ (2)
TC <sub>I</sub>	Temp. Coef., I <sub>SC</sub>		+0.2		%/°C	(1)
V <sub>BR</sub>	Reverse Breakdown Voltage	50			V	I <sub>R</sub> =100μA
λ <sub>P</sub>	Maximum Sensitivity Wavelength		930		nm	
λ <sub>R</sub>	Sensitivity Spectral Range	400		1100	nm	
θ <sub>1/2</sub>	Acceptance Half Angle		40		deg	(off center-line)

Specifications subject to change without notice.

103189 REV 0